

# ELITE; DESIGNER; BATON S; BATON L; CHEVRON S; CHEVRON L & RISTRETTO - 14P

## CE Declaration of Performance (DoP)

IN ACCORDANCE WITH CONSTRUCTION PRODUCTS REGULATION (EU) NO. 305/2011

### DOP 220014P

1. Unique identification code of the product-type: Pre-lacquered or oiled wooden floor covering with surface coating (groups below) / EN 14342
2. Type, batch or serial number or any other element allowing identification of the construction product: Cabbani Elite 14P; Cabbani Designer 14P; Cabbani Baton S 14P; Cabbani Baton L 14P; Cabbani Chevron S 14P; Cabbani Chevron L 14P & Cabbani Ristretto 14P
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: The products are intended for use as floor coverings(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 14342
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): Cabannes SAS, 1 Chemin du Cassard - FR 17210 CHEVANCEAUX. Produced at same location.
5. Name and contact address of the authorised representative: Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 3 (of Appendix ZA.2 of EN 14342 : 2013)
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.  
Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports.
  - Determination of formaldehyde emissions according (EN 717-1): Wood.be, Hof ter Vleestdreef 3, 1070 Anderlecht Belgium Test report 221099-REQ1 (4)
  - Determination of the slip resistance: Siège social, 84 avenue Jean Jaurès, Champs-sur-Marne, 77447 Marne-la-Vallée, cedex 2 Test report DSR-G-23-15851-1, DSR-G-23-15851-2 & DSR-G-23-15851-3
  - Determination of the thermal conductivity (EN 12667): Siège social, 84 avenue Jean Jaurès, Champs-sur-Marne, 77447 Marne-la-Vallée, cedex 2 Test report DEB 22 87026 (C)
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable
9. Declared performance: EN14342:2013 Wood Flooring

Unique identification code of the product-type: Pre-lacquered or oiled wooden floor covering with surface coating (groups below) / EN 14342

Product specifications:

- Birch plywood core with 2 sides of veneer
- Finished with  $\pm 80$  g/m<sup>2</sup> UV- lacquer or  $\pm 20$  g/m<sup>2</sup> UV-oil

Product	DOP nr	Mean Density (kg/m <sup>3</sup> )	Total Thickness (mm)	Backing	Reaction to Fire (EN14342 table 1) (Class)	Formaldehyde Emission (EN 717-1) (Class)	Content PCP (EN 14342) (ppm)	Slip resistance (CEN/TS 15676) (USRV)		Thermal conductivity (EN 12667) (W/m*K)	Biological Durability (EN 335) (Class)	Dimensions (mm)	Installation method
								Dry surface	Wet surface				
ELITE 14P	220014P	780	14	Veneer	Dfl-s1	E1	<5	<i>(Laquer)</i> 103	<i>(Laquer)</i> 34	0.13	1	1940x150x14	Floating or fully glued
DESIGNER 14P												1940x194x14	
BATON-S 14P												610x92x14	
BATON-L 14P												710x124x14	
CHEVRON-S 14P												600x92x14	
CHEVRON-L 14P												700x124x14	
RISTRETTO 14P												1420x92x14	

Benoît Cabannes

Plant Manager

Date:

01/05/2023

