BATON S 14P

CE Declaration of Performance (DoP)



Issued in accordance with the construction products directive (CPD) Nr; 18CB14P

This is to certify that in compliance with the Council Directive 89/106/EEC of 21st December 1988 on construction products, as amended.

Cabannes SAS, Le Cabaret - FR 17210 CHEVANCEAUX

Produced at same location.

Declares that the product detailed below conform to type as required by the above Directives as evidenced by the conformity Route below under attestation system 3 of Appendix ZA.2 of EN 14342 : 2013

Applied Harmonized Standards ; EN14342 : 2013 Wood Flooring

Characteristic	Standard	Performance declaration
Reaction to fire	Linked with the	Dfl-s1 / M4
	mean density	780 kg/m³
	Linked with the	+/- 14 mm
	minimum overall	
	thickness	
Emission of	EN 717-1	E1
formaldehyde		
Content of PCP	CEN/TR 14823	< 5 ppm
Breaking strength	EN 1533	NPD
Slipperiness	EN 1339 Annex J	NPD
Thermal	EN 12664	0.17 W/mK
conductivity		
Biological durability	EN 335	Class 1

Manufacturer's product: Cabannes SAS with specifications;

- 610 x 92 x 14 mm
- · Birch plywood core with 2 sides of veneer
- Finished with ±80 g/m² UV- lacquer or 20g/m² UV-Oil
- Pre-lacquered/oiled veneer wooden flooring
- Floating or fully glued installation for indoor use

Standards applicable; EN 14342

Benoît Cabannes

C.E.O.

Date: 01/01/2019