## **CHEVRON S 10H**





Issued in accordance with the construction products directive (CPD) Nr; 18CB10H

This is to certify that in compliance with the Council Directive 89/106/EEC of 21st December 1988 on construction products, as amended.

Cabannes SAS, Le Cabaret - FR 17210 CHEVANCEAUX

Produced at same location.

Declares that the product detailed below conform to type as required by the above Directives as evidenced by the conformity Route below under attestation system 3 of Appendix ZA.2 of EN 14342 : 2013

Applied Harmonized Standards ; EN14342 : 2013 Wood Flooring

| Characteristic           | Standard        | Performance declaration |
|--------------------------|-----------------|-------------------------|
| Reaction to fire         | Linked with the | Dfl-s1 / M4             |
|                          | mean density    | 850 kg/m³               |
|                          |                 |                         |
|                          | Linked with the | +/- 10 mm               |
|                          | minimum overall |                         |
|                          | thickness       |                         |
| Emission of formaldehyde | EN 717-1        | E1                      |
|                          |                 |                         |
| Content of PCP           | CEN/TR 14823    | < 5 ppm                 |
| Breaking strength        | EN 1533         | NPD                     |
| Slipperiness             | EN 1339 Annex J | NPD                     |
| Thermal conductivity     | EN 12664        | 0.15 W/mK               |
| Biological durability    | EN 335          | Class 1                 |

Manufacturer's product : Cabannes SAS with specifications;

- 600 x 92 x 10 mm
- HDF core with 2 sides of veneer
- Finished with ±80 g/m² UV- lacquer or ±20 g/m² UV-oil
- Pre-lacquered or oiled veneer wooden flooring
- Floating and fully glued installation for indoor use

Standards applicable; EN 14342

Benoît Cabannes

C.E.O.

Date: 01/01/2019