



MAINTENANCE OIL

PRODUCT DESCRIPTION

A mix of resins and natural oils to protect and maintain oiled wooden floors and floors treated with UV-oil.

TECHNICAL DATA

APPEARANCE	Yellow fluid
PHYSICAL STATE	Thick fluid
ODOR	Linseed oil
IGNITION POINT	Above 61°C
WATER SOLUBILITY	No
DENSITY	Ca. 0,83

PRELIMINARY TREATMENT

Remove the dirt and the soap residue with the 'Cabbani Intensive Cleaner' and clear water. Let it dry completely.

INSTRUCTIONS

Stir well before using. Apply a thin and equal layer 'Cabbani Maintenance Oil' with a cloth, mop or floor polisher with a white or beige pad. Allow it to penetrate a few minutes. Rub or polish until the oil has penetrated the wood. Then, clean the surface a last time with a dry cloth without fluffs.

DRYING TIME

Leave the floor clear of furniture for 12 hours. Do not clean the floor with water during that period.

SPREADING CAPACITY

50 m²/l.

FURTHER TREATMENT

It is recommended to repeat the treatment at least once a year, even twice if there's floor heating. Use the 'Cabbani Parquet Soap' for regular cleaning.

SPECIFIC INFORMATION

Plunge the cloths or pads in water after using due to combustion hazard. Use as little water as possible on wooden floors. Too much water can damage your floors. Safety requirements: Keep out of the reach of children
More information: www.cabbani.com

Cabbani[®] products are destined for professional and private users. The instructions in the technical data sheet were written based on the necessary tests and years of experience. We invested our utmost knowledge and capacities whilst writing these instructions. The user must thus test this product according to the circumstances and his/her possibilities. Therefore, this technical data sheet cannot be guaranteed.