

VERSAILLES - 15P

DESCRIPTION

2-layer parquet: top layer European Oak / 100% Eucalyptus plywood

Total Thickness	15 mm	
Thickness Top Layer	4 mm	
Connection	Tongue and groove	
Bevels	On 4 sides	
Available sizes	Versailles	1000x1000x15
Available qualities	Select/Rustic Light Aged	
Possible Collections	Select: 1/2/3/4/5 Rustic light Aged: 2/4/5	
Strips	1-strip	

NORMS & CLASSIFICATION

Thermal resistance	0,11 m²K/W
Thermal conductivity	0,14 W/mK
Usage Class XP B53-669	31

CE certification conform to norm EN14342
VOC emission classification A+
Guarantee on the concept (cf. guarantee terms and conditions)

Moisture content when leaving the company : 9% ±2%.
Fits in dry spaces with a relative humidity of 40 to 60%.
Fire reaction: Dfl-s1

Formaldehyde emission (EN 717-1): E1

The conditions of use and installation on heated and reversible floors must be known and scrupulously applied, consult the installation instructions in the packages and the website www.cabbani.com .	Resandable	2 x
	COMPATIBILITY FLOOR HEATING	
	Water circulation	yes
	Radiant	yes
	Reversible	yes

EVOLUTION

Wood is a product of nature, therefore every single board is different (structure, colour,...).

When stained, the wooden floor will be more homogenous. Natural oak has the tendency to evolve into a more brownish or yellowish colour. The colour of stained oak stays relatively stable.

CABBANI®'s maintenance products have a nourishing and revitalising effect and therefore restore the parquet's natural beauty.

INSTALLATION AND MAINTENANCE

The installation and maintenance should be executed professionally and according to the recommendations of the manufacturer. See the installation instructions on www.cabbani.com/en/downloads. The floor can only be glued down. Please contact the glue manufacturer with questions related to the glue in question. The UV lacquer finish is solvent, VOC and formaldehyde free. The matt lacquer corresponds to gloss 5 (±3), the satin lacquer corresponds to gloss 20 (±3). The UV oil finish uses a solvent free UV oil. Please consult the maintenance guide before using or maintaining this product..



Cabannes SAS, 1 Chemin du Cassard,
17210 Chevenceaux-France
tel +33 5 46 04 66 88 (FR) - tel +32 56 52 88 49 (NL/EN)
info@cabbani.com

www.cabbani.com