

## ELITE & DESIGNER - 19P

### DESCRIPTION

3-layer parquet/wooden floor : top layer European Oak / 100% Birch plywood / Stabilising backing in rotary cut veneer

Total Thickness	19 mm	
Thickness Top Layer	5,5 mm	
Connection	Tongue and groove	
Bevels	On 2 sides	
Available sizes	Elite Designer	1940x150x19 1940x194x19
Available qualities	Select/Rustic Light/Rustic Nature	
Possible Collections	Collection 1/2/3/4/5	
Strips	1-strip	

### NORMS & CLASSIFICATION

Thermal resistance	0,13 m²K/W
Thermal conductivity	0,15 W/mK
Usage Class XP B53-669	33

PEFC 10-31-1213 classification (from sustainably managed forests)  
FSC FCBA-COC-000366 (on demand)  
CE certification conform to norm EN14342  
VOC emission classification A+  
Guarantee on the concept (cf. guarantee terms and conditions)  
100% made in France  
Moisture content when leaving the company : 9% ±2%.  
Fits in dry spaces with a relative humidity of 40 to 60%.  
Fire reaction: Cfl-s1  
Formaldehyde emission (EN 717-1): E1

Cabannes SAS, 1 Chemin du Cassard,  
17210 Chevanceaux-France  
tel +33 5 46 04 66 88 (FR) - tel +32 56 52 88 49 (NL/EN)  
info@cabbani.com

[www.cabbani.com](http://www.cabbani.com)

The conditions of use and installation on heated and reversible floors must be known and scrupulously applied, consult the installation instructions in the packages and the website <a href="http://www.cabbani.com">www.cabbani.com</a> .	Resandable	3 x
	<b>COMPATIBILITY FLOOR HEATING</b>	
	Water circulation	no
	Radiant	no
	Reversible	no

### EVOLUTION

Wood is a product of nature, therefore every single board is different (structure, colour,...).

When stained, the wooden floor will be more homogenous. Natural oak has the tendency to evolve into a more brownish or yellowish colour. The colour of stained oak stays relatively stable.

CABBANI®'s maintenance products have a nourishing and revitalising effect and therefore restore the parquet's natural beauty.

### INSTALLATION AND MAINTENANCE

The installation and maintenance should be executed professionally and according to the recommendations of the manufacturer. See the installation instructions on [www.cabbani.com/en/downloads](http://www.cabbani.com/en/downloads). The floor can be glued down or floating. Please contact the glue manufacturer with questions related to the glue in question. The UV lacquer finish is solvent, VOC and formaldehyde free. The matt lacquer corresponds to gloss 5 (±3), the satin lacquer corresponds to gloss 20 (±3). The UV oil finish uses a solvent free UV oil. Please consult the maintenance guide before using or maintaining this product.



PEFC™ and FSC® are available from 500m².

