

# BÂTON 14P (BIRCH PLYWOOD)

# **DESCRIPTION**

3-layer Herringbone pattern floor : top layer European Oak / 100% Birch plywood / Stabilising backing in rotary cut veneer. Tongue and groove system on 4 sides. Bevels on the 4 sides. Dimensional tolerance of  $\pm$  0,2mm.

	BÂTON 14P				BÂTON 14P	
Total thickness	14 mm				14 mm	
Thickness top layer	3,2 mm				3,2 mm	
Sizes available	610 x 92mm				710 x 124 mm	
Qualities available	Select	Rustic			Select	Rustic
Possible collections	01 02	01 02 03 04 05 di Lorenzo			01 02	01 02 03 04 05 di Lorenzo
Strips	1 strip				1 s	trip

### NORMS AND CLASSIFICATION

	BÂTON 1 <b>4</b> P	BÂTON <b>14</b> P
Thermal resistance	0,08 m <sup>2</sup> K/W	0,08 m <sup>2</sup> K/W
Thermal conductivity	0,17 W/mK	0,17 W/mK
Usage Class (oak)	31	31

Wood originally from French and European forests (oak) PEFC 10-31-1213 classification (from sustainably managed forests)

FSC FCBA-COC-000366 (optional on demand) CE certification conform to norm EN14342

Sanitary classification A+ (granted by the FCBA)

15 years guarantee on the concept (cf. guarantee terms and conditions)

100% made in France

Moisture content when leaving the company:  $9\% \pm 2\%$ . Fits in dry spaces with a relative humidity of 40 to 60%.

Fire reaction: Dfl s1 / M4 Formaldehyde emission: E1

# INSTALLATION AND MAINTENANCE

The installation and maintenance should be executed professionally and according to the recommendations of the manufacturer.

See the installation instructions on www.cabbani.com/en/downloads.

The floor can be glued down or floating. Please contact the glue manufacturer with questions related to the glue in question. The UV lacquer finish is solvent, VOC and formaldehyde free. The matt lacquer corresponds to gloss 7 (±3), the satin lacquer corresponds to gloss 20 (±3).

The UV oil finish uses a solvent free UV oil.

Please consult the maintenance guide before using or maintaining this product

maintaining this product. To simplify the calculation and installation of pattern flooring, we developed an easy-to-use app : patterns.cabbani.com

	BÂTON 1 <b>4</b> P		BÂTON <b>14</b> P	
Resandable	2x		2x	
COMPATIBILITY FLO				
Hot water circulation	yes		yes	
Radiant heating	yes		yes	
Reversible	yes		yes	

Make sure to be aware of the installation and using guidelines for the floor heating. Please follow thoroughly the valid instructions and contact the manufacturer.

#### **EVOLUTION**

Wood is a product of nature, therefore every single board is different (structure, colour,...). When stained, the wooden floor will be more homogenous. Natural oak has the tendency to evolve into a more brownish or yellowish colour. The colour of stained oak stays relatively stable.

CABBANI®'s maintenance products have a nourishing and revitalising effect and therefore restore the parquet's natural beauty.











