

## CHEVRON 14H (HDF)

### DESCRIPTION

3-layer chevron pattern floor : top layer European Oak / HDF core / Stabilising backing in rotary cut veneer.  
 Tongue and groove system on 4 sides.  
 Bevels on the 4 sides. Dimensional tolerance  $\pm 0,2\text{mm}$ .

	CHEVRON S 14H		CHEVRON L 14H	
Total thickness	14 mm		14 mm	
Thickness top layer	3,2 mm		3,2 mm	
Sizes available	600 x 92 mm		700 x 124 mm	
Qualities available	Select	Rustic	Select	Rustic
Possible collections	01 02	01 02 03 04 05	01 02	01 02 03 04 05
Strips	1 strip		1 strip	

### NORMS AND CLASSIFICATION

	CHEVRON S 14H	CHEVRON L 14H
Thermal resistance	0,081 m <sup>2</sup> K/W	0,081 m <sup>2</sup> K/W
Thermal conductivity	0,172 W/mK	0,172 W/mK
Usage Class (oak)	23/31	23/31

Wood originally from French and European forests (oak)  
 PEFC 10-31-1213 classification (from sustainably managed forests)  
 FSC FCBA-COC-000366 (optional on demand)  
 CE certification conform to norm EN14342  
 Sanitary classification A+ (granted by the FCBA)  
 15 years guarantee on the concept (cf. guarantee terms and conditions)  
 100% made in France  
 Moisture content when leaving the company : 9%  $\pm 2\%$ .  
 Fits in dry spaces with a relative humidity of 40 to 60%.  
 Fire reaction: DFL s1/M4  
 Formaldehyde emission: E1

### INSTALLATION AND MAINTENANCE

The installation and maintenance should be executed professionally and according to the recommendations of the manufacturer.

See the installation instructions on [www.cabbani.com/en/downloads](http://www.cabbani.com/en/downloads).

The floor can be glued down or floating. Please contact the glue manufacturer with questions related to the glue in question.

The UV lacquer finish is solvent, VOC and formaldehyde free.

The matt lacquer corresponds to gloss 7 ( $\pm 3$ ), the satin lacquer corresponds to gloss 20 ( $\pm 3$ ).

The UV oil finish uses a solvent free UV oil.

Please consult the maintenance guide before using or maintaining this product.

To simplify the calculation and installation of pattern flooring, we developed an easy-to-use app : [patterns.cabbani.com](http://patterns.cabbani.com)

	CHEVRON S 14H	CHEVRON L 14H
Resandable	2x	2x
<b>COMPATIBILITY FLOOR HEATING</b>		
Hot water circulation	yes	yes
Radiant heating	yes	yes
Reversible	no	no

Make sure to be aware of the installation and using guidelines for the floor heating. Please follow thoroughly the valid instructions and contact the manufacturer.

### EVOLUTION

Wood is a product of nature, therefore every single board is different (structure, colour,...). When stained, the wooden floor will be more homogenous. Natural oak has the tendency to evolve into a more brownish or yellowish colour. The colour of stained oak stays relatively stable.

CABBANI®'s maintenance products have a nourishing and revitalising effect and therefore restore the parquet's natural beauty.

