

ELITE P (BIRCH PLYWOOD)

DESCRIPTION

3-layer parquet/wooden floor : top layer European Oak / 100% Birch plywood / Stabilising backing in rotary cut veneer.
Tongue and groove system on 4 sides.
Bevels on the 2 long sides. Dimensional tolerance of $\pm 0,2\text{mm}$.

	ELITE 10P		ELITE 14P		ELITE 19P	
Total thickness	10 mm		14 mm		19 mm	
Thickness top layer	2 mm		3,2 mm		5,5 mm	
Sizes available	1940 x 150 mm		1940 x 150 mm		1940 x 150 mm	
Qualities available	Select	Rustic	Select	Rustic	Select	Rustic
Possible collections	01 02	01 02 03 04 05 diLorenzo	01 02	01 02 03 04 05 diLorenzo	01 02	01 02 03 04 05 diLorenzo
Strips	1 strip		1 strip		1 strip	

NORMS AND CLASSIFICATION

	ELITE 10P	ELITE 14P	ELITE 19P
Thermal resistance	0,07 m ² K/W	0,08 m ² K/W	0,11 m ² K/W
Thermal conductivity	0,15 W/mK	0,17 W/mK	0,17 W/mK
Usage Class (oak)	23/31	31	33

Wood originally from French and European forests (oak)
PEFC 10-31-1213 classification (from sustainably managed forests)
FSC FCBA-COC-000366 (optional on demand)
CE certification conform to norm EN14342
Sanitary classification A+ (granted by the FCBA)
15 years guarantee on the concept (cf. guarantee terms and conditions)
100% made in France
Moisture content when leaving the company : 9% $\pm 2\%$.
Fits in dry spaces with a relative humidity of 40 to 60%.
Fire reaction:
Cfl s1 / M3 for 19mm,
Dfl s1 / M4 for 10 & 14mm.
Formaldehyde emission: E1

INSTALLATION AND MAINTENANCE

The installation and maintenance should be executed professionally and according to the recommendations of the manufacturer.
See the installation instructions on www.cabbani.com/en/downloads.

The floor can be glued down or floating. Please contact the glue manufacturer with questions related to the glue in question.
The UV lacquer finish is solvent, VOC and formaldehyde free.
The matt lacquer corresponds to gloss 7 (± 3), the satin lacquer corresponds to gloss 20 (± 3).
The UV oil finish uses a solvent free UV oil.
Please consult the maintenance guide before using or maintaining this product.

	ELITE 10P	ELITE 14P	ELITE 19P
Resandable	1x	2x	3x
COMPATIBILITY FLOOR HEATING			
Hot water circulation	yes	yes	no
Radiant heating	yes	yes	no
Reversible	yes	yes	no

Make sure to be aware of the installation and using guidelines for the floor heating. Please follow thoroughly the valid instructions and contact the manufacturer.

EVOLUTION

Wood is a product of nature, therefore every single board is different (structure, colour,...). When stained, the wooden floor will be more homogenous. Natural oak has the tendency to evolve into a more brownish or yellowish colour. The colour of stained oak stays relatively stable.

CABBANI®'s maintenance products have a nourishing and revitalising effect and therefore restore the parquet's natural beauty.

