

RISTRETTO 14P (BIRCH PLYWOOD)

DESCRIPTION

3-layer wooden floor : top layer European Oak / 100% Birch plywood / Stabilising backing in rotary cut veneer. Tongue and groove system on 4 sides.
Bevels on the 2 sides. Dimensional tolerance of $\pm 0,2\text{mm}$.

| | RISTRETTO 14P | | | |
|----------------------|---------------|--|--|--|
| Total thickness | 14 mm | | | |
| Thickness top layer | 3,2 mm | | | |
| Sizes available | 1420 x 92mm | | | |
| Qualities available | Select | Rustic | | |
| Possible collections | 01 02 | 01 02 03 04 05 di Lorenzo | | |
| Strips | 1 strip | | | |

NORMS AND CLASSIFICATION

| | RISTRETTO 14P | | | |
|----------------------|-------------------------|--|--|--|
| Thermal resistance | 0,08 m ² K/W | | | |
| Thermal conductivity | 0,17 W/mK | | | |
| Usage Class (oak) | 31 | | | |

Wood originally from French and European forests (oak)
PEFC 10-31-1213 classification (from sustainably managed forests)
FSC FCBA-COC-000366 (optional on demand)
CE certification conform to norm EN14342
Sanitary classification A+ (granted by the FCBA)
15 years guarantee on the concept (cf. guarantee terms and conditions)
100% made in France
Moisture content when leaving the company : 9% \pm 2%.
Fits in dry spaces with a relative humidity of 40 to 60%.
Fire reaction: Dfl s1 / M4
Formaldehyde emission: E1

INSTALLATION AND MAINTENANCE

The installation and maintenance should be executed professionally and according to the recommendations of the manufacturer.

See the installation instructions on www.cabbani.com/en/downloads.

The floor can be glued down or floating. Please contact the glue manufacturer with questions related to the glue in question.

The UV lacquer finish is solvent, VOC and formaldehyde free.

The matt lacquer corresponds to gloss 7 (± 3), the satin lacquer corresponds to gloss 20 (± 3).

The UV oil finish uses a solvent free UV oil.

Please consult the maintenance guide before using or maintaining this product.

| | RISTRETTO 14P | | | |
|------------------------------------|---------------|--|--|--|
| Resandable | 2x | | | |
| COMPATIBILITY FLOOR HEATING | | | | |
| Hot water circulation | yes | | | |
| Radiant heating | yes | | | |
| Reversible | yes | | | |

Make sure to be aware of the installation and using guidelines for the floor heating. Please follow thoroughly the valid instructions and contact the manufacturer.

EVOLUTION

Wood is a product of nature, therefore every single board is different (structure, colour,...). When stained, the wooden floor will be more homogenous. Natural oak has the tendency to evolve into a more brownish or yellowish colour. The colour of stained oak stays relatively stable.

CABBANI[®]'s maintenance products have a nourishing and revitalising effect and therefore restore the parquet's natural beauty.

